

## Specifications Table for FTXF-E / RXF-E

				FTXF20E5V1B / RXF20E5V1B	FTXF25E5V1B / RXF25E5V1B	FTXF35E5V1B / RXF35E5V1B	FTXF42E5V1B / RXF42E5V1B
Cooling capacity	Min.		kW	1.3	1.3	1.3	1.4
	Max.		kW	2.4	2.8	3.8	4.3
	Nom.		kW	2.00	2.50	3.30	4.20
Space cooling	SEER			6.50	6.50	6.50	6.50
	Annual energy consumption		kWh/a	108	135	188	226
	Capacity	Pdesign	kW	2.00	2.50	3.50	4.20
	Energy efficiency class			A++	A++	A++	A++
Space heating (Average climate)	Capacity	Pdesign	kW	2.20	2.40	2.60	3.30
	SCOP/A			4.20	4.20	4.20	4.30
	Energy efficiency class			A+	A+	A+	A+
	Pdh Heating capacity at -10°		kW	1.86	1.97	2.21	2.61
	Annual energy consumption		kWh/a	733	801	867	1,075
Nominal efficiency	EER			3.38	3.24	3.30	3.30
	COP			3.75	3.73	3.72	3.71
	Energy labeling Directive	Cooling		A	A	A	A
		Heating		A	A	A	A
Heating capacity	Nom.		kW	2.40	2.80	3.50	4.60
	Min.		kW	1.30	1.30	1.30	1.40
	Max.		kW	3.30	3.70	4.40	5.00
Notes				(1) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified	(1) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified	(1) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified	(1) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified

	(2) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series	(2) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series	(2) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series	(2) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series
	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data

^